WALLPOD:EV

FREE-TO-USE

Type 2, Mode 3 Charging Socket
3.6kW or 7.2kW

ROLEC
EV Charging

MANUFACTURED IN THE UK







The WALLPOD:EV is a low-cost, entry level home charging unit, designed to offer full Mode 3 fast charging to every Electric Vehicle (EV/PHEV) on the market today.

This charging unit is available with a Type 2, Mode 3 charging socket offering either 3.6kW (16A) or 7.2kW (32A) charging speeds, and is equipped with built-in TruePEN PME fault detection.


PRODUCT FEATURES

- Mode 3 (IEC 61851-1) fast charging
- Type 2 (IEC 62196) charging socket
- 3.6kW (16A) & 7.2kW (32A) charging speeds
- Built-in overload and fault current protection (Type A RCBO)
- Built-in TruePEN PME fault detection, no earth electrode/rod required
- Built-in DC sensitive protective device
- Built-in LED charging status indicator
- Easy to install and maintain
- IP Rated
- UV stabilised
- Corrosion resistant
- Fire retardant
- IK10 impact resistant design



SPECIFICATIONS

Product Code	EVWP7C1D-PTN / EVWP7C2D-PTN
Charging Socket	Type 2 (IEC 62196-2)
AC Charging Output	3.6kW (16A) / 7.2kW (32A)
Charge Protocol	Mode 3
Overload & Fault Current Protection	Built-in 20A, 30mA Type A (RCBO) & Built-in 6mA DC Sensitive Device / Built-in 40A, 30mA Type A (RCBO) & Built-in 6mA DC Sensitive Device
Earthing	Built-in TruePEN PME Fault Detection
Input Supply	16A 230V AC/50Hz (Single Phase) / 32A 230V AC/50Hz (Single Phase)
Cable Terminals	2x 16mm²
Standby Consumption	Approx 0.05kWh per day
Certifications & Compliances	EV Charging Compliance - EN 61851-1:2019, EN 61851-22:2002 Wiring Regulations - BS 7671:2018 EMC Compliance - EN 61000-6-1:2007+A1:2011, EN 61000-6-3:2007 Safety Compliance (LVD) - EN 62196-1:2014, 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 Environmental Protection - Enclosure IP65, Socket IP54 (BS EN 60529:1992+A2:2013), Enclosure IK10 (EN 62262:2002) RCBU - IEC 61009-1:2010+A1+A2+A11+A12, IEC 61009-2-2:1991 Contactor - IEC 60947-4-1:2018, IEC 62955:2009 RoHS - 2011/65/EU (The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012) REACH - 1907/2006
Dimensions	179mm x 367mm x 142mm (H x W x D)
Unit Material	Polycarbonate (UV Resistant)
Operating Temperature	-30°C to +50°C
Standard Base Colour	Warm White (Other colours available on request)
Standard Pod Colour	Green (Other colours available on request)






OPTIONS & ACCESSORIES

- Key switch control charging
- Lockable door to switchgear
- Built-in class 1 **MID** compliant kWh meter
- Built-in time clock providing charge time management
- Corporate branding (colours, logo badge, etc.)
- Amp-Selector key switch (switches between 16A or 32A)
- Charge-By-Solar switch (switches between 6A, 13A, 16A or 32A)
- Charge point signage
- EV charging cables (Type 1 to Type 2 or Type 2 to Type 2)





Head office contact:
T: +44 (0) 1205 724754
F: +44 (0) 1205 724876
Rolec Services Ltd
Rapps Lane, Frampton West
Boston, Lincolnshire
UK, PE20 1QU
@RolecEV
/Rolec-Services
www.rolecserv.com



SELECTED MODEL OUTLINED IN RED