the Rooflight Company

Wychwood Business Centre
Milton Road
Shipton-under-Wychwood
Oxfordshire OX7 6XU

Tel: 01993 833155
info@therooflightcompany.co.uk
www.therooflightcompany.co.uk

Technical Data Sheet

The Conservation Plateau Rooflight (standard sizes)



Product Description

The Conservation Plateau Rooflight is the only flat rooflight designed specifically for heritage buildings.

Manufactured From

3mm mild steel with a protective polyester powder coating to BS EN ISO 12944.

The standard frame is finished in a textured semi-gloss paint finish in black RAL 9005 (other RAL colour options are available).

All Conservation Plateau Rooflights have internal linings which have a multi coat paint finish applied and sealed with a white coating (to a 10% gloss level).

COASTAL: Please note, for properties that reside within 5km of the coastline or large estuary, we recommend calling our Customer Services Team on 01993 833155 to discuss an appropriate alternative of stainless steel.

Pitch

Suitable for flat roof installations with a 3°-10° roof pitch.

Standard Glazing

4mm Toughened Outer.

16mm 90% Argon Cavity.

6.4mm Laminated Low Emissivity (Low e) Inner.

Achieves a whole-unit U-Value of 1.8W/m2K (in the vertical plane), 1.9W/m2K (in the horizontal plane) in accordance with BS EN ISO 10077-2:2017.

Other glazing specifications are available upon request, contact us for more information.

Sizes and Prices (internal structural kerb)

PL01	(W) 625mm x (L) 625mm	**£1019**
PL02	(W) 925mm x (L) 925mm	**£1569**
PL03	(W) 1225mm x (L) 1225mm	**£2147**
PL04	(W) 1525mm x (L) 1525mm	**£2477**
PL07	(W) 925mm x (L) 625mm	**£1373**
PL08	(W) 1225mm x (L) 625mm	**£1636**
PL09	(W) 1225mm x (L) 925mm	**£1963**
PL10	(W) 1525mm x (L) 925mm	**£2159**
PL11	(W) 1525mm x (L) 1225mm	**£2347**
PL12	(W) 2025mm x (L) 1525mm	**£3373**
PL18	(W) 2025mm x (L) 1025mm	**£2477**
PL22	(W) 925mm x (L) 1525mm	**£2159**
PL24	(W) 1025mm x (L) 2025mm	**£2477**

Prices exclude accessories, VAT and delivery. For Bespoke sizes please contact us on 01993 833155. Sizes listed are for the internal structural kerb.

All prices are correct at the time of going to press.

Opening Options

Manual hand winders
Available in brass or chrome with opening distances of either 150mm or 300mm.

Manual pole winder
Winding crank for out of reach opening. Available in brass or chrome with opening distances of 150mm or 300mm. Poles are available in varying lengths from 1m to 3m.

Motors
Motorised opening options are available for out of reach rooflights and can be controlled by a switch or remote. Contact us for more information.

Fixed Shut
A fixing bracket for a fixed shut roof window. The fixing bracket is white as standard.

Please note: The PL12 can only be fixed shut or motorised due to its size.

Optional Extras

Rain sensors, temperature sensors and other accessories are available on request. Please consult with us directly for compatibility.

Lead Time

The Conservation Plateau Rooflight is available within 12 - 35 working days depending on model size and specification configured. Subject to availability.

Installation

The Conservation Plateau Rooflight Installation Manual and Installation Drawings are available to download from our website.

BIM Objects can also be downloaded.

Warranty

Don't forget to extend your warranty for free.

Our steel rooflights benefit from an extended warranty of up to ten years*. Upon receipt of your rooflight, please register your product.

*Terms and conditions apply.

Upon product registration with us, the standard warranty can be extended to ten years, as set out in our Terms and Conditions, provided that the appropriate products have been installed to suit their location and that these are regularly maintained, with these actions recorded in accordance with our maintenance instructions. Register your product at

www.therooflightcompany.co.uk/contact/register-a-product



the Rooflight Company

Visit **www.therooflightcompany.co.uk** or call us today on **01993 833155** for more information.